

Technical Data Sheet

General Description

The FibaTape® family includes a complete range of innovative drywall joint tapes and reinforcing products for both professionals and DIYers.

The **self-adhesive** fabric for renovation FibaTape® Crackstop is easy to use and quick to apply. It is **glass-fiber** structure brings a strong and lasting reinforcement and only needs a light finishing layer of plaster or render. Its width allows covering **large cracks**.

Properties

- Self-adhesive
- High mechanical strength
- Smooth finish



Edited by:

ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovska 106

CZ – 570 01 Litomyšl

Tel: + 420 461 651 111

Fax: + 420 461 612 769

www.adfors.com

ADFORS Construction Products Europe reserves the right to change the information given herein without prior notice

Last update: 12.12.2017

Technical Characteristics

Technical Characteristics		
Setting of the fiberglass yarns (informative value)	Warp	Weft
	35,4 ends / 10 cm 9 ends / inch	35,4 ends / 10 cm 9 ends / inch
Treated fabric weight (incl. glue) (informative value)	(64,5 ± 3,5) g / m ² (1,90 ± 0,10) oz / yd ²	
DPU (PES + coating + PSA) (informative value)	41 – 47 %	
Thickness (informative value)	0,26 mm	
	0,01 inch	
Tensile strength	Warp	Weft
	260 N / 2,54 cm 57 lbs / inch	483N / 2,54 cm 106 lbs / inch
Dimensions & Packaging		
Standard width ⁽¹⁾ (individual value)	150 ± 2 mm	
	5,9 inch	
Standard roll length ⁽¹⁾ (individual value)	25 m (± 2 %)	
	98,4 yd (± 2 %)	
Rolls / box ⁽¹⁾	12	
Rolls / pallet ⁽¹⁾	540 (45 boxes)	
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C.	
Pallet (non-returnable) ⁽¹⁾	80 x 120 x 100 cm	
Quality Control		
Traceability ⁽¹⁾	Batch no. marked on the box	

⁽¹⁾ Other dimension or features on request