

Technical Data Sheet

General Description

The FibaTape® family includes a complete range of innovative drywall joint tapes and reinforcing products for both professionals and DIYers.

FibaTape® Xtreme is a self-adhesive tape made of fiberglass that can be applied in all conditions: thanks to its high tack, it performs well in winter when the temperature is low and humidity can increase during the day.

Technical Characteristics

Technical Characteristics		
Setting of the fiberglass yarns (informative value)	Warp	Weft
	36 ends / 10 cm 9 ends / inch	36 ends / 10 cm 9 ends / inch
Treated fabric weight (incl. glue) (informative value)	(66,5 ± 3,5) g / m ² (1,96 ± 0,10) oz / yd ²	
DPU (PES + coating + PSA) (informative value)	43 – 48 %	
Thickness (informative value)	0,26 mm 0,01 inch	
	Warp	Weft
Tensile strength	260 N / 2,54 cm 57 lbs / inch	483 N / 2,54 cm 106 lbs / inch
	Dimensions & Packaging	
Standard width ⁽¹⁾ (individual value)	(48 ± 2) mm (1,89 ± 0,08) inch	
	Standard roll length ⁽¹⁾ (individual value)	
Standard roll length ⁽¹⁾ (individual value)	90 m (± 2 %) 98,43 yd (± 2 %)	
Rolls / box ⁽¹⁾	12	
Rolls / pallet ⁽¹⁾	480 (40 boxes)	
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C.	
Pallet (non-returnable) ⁽¹⁾	80 x 120 x 100 cm	
Quality Control		
Traceability ⁽¹⁾	Batch no. marked on the box	

⁽¹⁾ Other dimension or features on request

Properties

- Extreme tack
- For extreme humidity – 90 % RH
- For extreme temperature
- Self-adhesive
- High mechanical strength
- Smooth finish



Edited by:

ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovska 106

CZ – 570 01 Litomyšl

Tel: + 420 461 651 111

Fax: + 420 461 612 769

www.adfors.com

ADFORS Construction Products Europe reserves the right to change the information given herein without prior notice

Last update: 12.12.2017