

## Technical Data Sheet

### General Description

The FibaTape® family includes a complete range of innovative drywall joint tapes and reinforcing products for both professionals and DIYers.

The FibaTape® Mold-X is self-adhesive tape made of fiberglass and treated with a special coating to prevent mold development. It is the best tape to be used in combination with mold-resistant plasterboards and for wet room.

### Properties

- Anti-Mold (ASTM D3273)
- Self-adhesive
- High mechanical Strength
- Smooth finish

### Technical Characteristics

Technical Characteristics		
Setting of the fiberglass yarns (informative value)	Warp	Weft
	35,4 ends / 10 cm 9 ends / in	35,4 ends / 10 cm 9 ends / in
Treated fabric weight (incl. glue) (informative value)	64,5 ± 3,5 g / m <sup>2</sup> 1,90 ± 0,10 oz / yd <sup>2</sup>	
DPU (PES + coating + PSA) (informative value)	41 – 47 %	
Thickness (informative value)	0,26 mm 0,01 inch	
	Warp	Weft
Tensile strength	260 N / 2,54 cm 57 lbs / inch	483 N / 2,54 cm 106 lbs / in
	Dimensions & Packaging	
Standard width <sup>(1)</sup> (individual value)	48 ± 2 mm 1,89 ± 0,08 inch	
	Standard roll length <sup>(1)</sup> (individual value)	
90 m (± 2 %) 98,43 yd (± 2 %)		
Rolls / box <sup>(1)</sup>	12	
Rolls / pallet <sup>(1)</sup>	480 (40 boxes)	
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C.	
Pallet (non-returnable) <sup>(1)</sup>	80 x 120 x 100 cm	
Quality Control		
Traceability <sup>(1)</sup>	Batch no. marked on the box	



Edited by:

**ADFORS Construction Products Europe**

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovska 106

CZ – 570 01 Litomyšl

Tel: + 420 461 651 111

Fax: + 420 461 612 769

[www.adfors.com](http://www.adfors.com)

**ADFORS Construction Products Europe** reserves the right to change the information given herein without prior notice

Last update: 12.12.2017

<sup>(1)</sup> Other dimension or features on request