

NOVELIO

CLASSIC



Self-adhesive fiberglass wall covering

Ideal solution for fast renovation

Saving time on construction work, a challenge for all

- How to prepare a wall or ceiling after a water damage **in only 2 steps?**
- How to renovate a room in **only one weekend?**



Novelio® EasyFix provides the solution with a high-performance product

Significant time savings thanks to its self-adhesive formulation

- **20% saving** in wall covering application time
- **30% saving** in total renovation work

A decorative, soft and resistant wall covering as are all products in the Novelio® range

- Reinforces delicate surfaces
- Resists abrasion and impact
- Covers all cracks

EasyFix paintable wall covering is produced with a **self-adhesive coating** on one side.

The chemical formulation of this adhesive **meets all needs of the applicator:**

- To keep the wall covering glued to the wall until ready for the painting
- To remove the strip several times without losing adhesiveness
- To work in all external conditions

EasyFix efficiency

20% saving in wall covering application time*.

Thanks to its adhesive system, the wall covering can be applied directly to the wall or ceiling. No need to glue the wall beforehand.

30% saving in a room renovation time*.

Once applied, the wall covering can be painted immediately. No need to wait 24 hours for the glue to dry. A room can be renovated in less than 2 days.

* Calculations are based on a typical application for a standard 15 m² room

Application advice:

- 1 - Apply the wall covering, smooth it and cut off the excess



Practical advice:

- Make sure that the surface is clean, dry and primed
- Check if the wall is vertical and apply the first strip
- Within 50 cm of the top, place the second strip adjacent to the first one to get a perfect joint. Then apply the whole length
- For technical sections, make a double cut to get a perfect joint
- Smooth the strip to remove air bubbles and check adhesiveness before starting the 2nd strip
- Apply the wall covering carefully in angles and cut off the excess

- 2 - Apply a second layer of acrylic paint immediately. Once fully dry, apply a second layer of acrylic paint



Practical advice:

- Respect the applications conditions of the paint producer
- The 1st layer must go through the wall covering to ensure firm adhesion to the wall
- If necessary, adjust the viscosity of the acrylic paint to ensure it spreads evenly
- Apply generously on the wall covering
- Do not use a diluted paint for the second layer to ensure a thick and durable film of paint

Saint-Gobain ADFORS CZ

Phone: +420 461 651 111