

Technical Data Sheet

General Description

Glass fiber wall covering is used to cover walls and other interior surfaces. Product is perfect for new spaces: thanks to its high mechanical properties it prevents cracks from appearing, consequently prolonging the surface lifetime. It is also a performing solution for light renovation: it covers crack and wall irregularities.

It is mainly used in residential buildings (houses, rented flats, corridors) and non-residential buildings (administrative buildings, hotels and hospital).

Technical characteristics

| Technical Characteristics | |
|---|---|
| Composition | 100 % coated glass fiber |
| Treated fabric weight (average value) | 130 g / m ² (± 8 %) |
| Oekotex certificate Standard 100 | Product Class III |
| Emission in indoor air | A+ (very low) |
| Fire resistance (EN 13501-1) | Euroclass B-s 1,d 0 |
| Recommendation for application | |
| Quantity of vinyl glue | 250 g / m ² (approximate) |
| Quantity of acrylic paint | 150 - 250 g / m ² (approximate) |
| Dimensions & Packaging | |
| Width (individual value) | 100 cm (± 1 %) |
| Roll length (individual value) ⁽¹⁾ | 50 m (± 1 %) |
| Roll direction ⁽¹⁾ | Paintable surface outside of roll |
| Roll packaging ⁽¹⁾ | Plastic foil |
| Label on roll ⁽¹⁾ | With installation instructions |
| Storage conditions | Dry room, storing temperature from -10 °C to +50 °C. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll. |
| Palette (non-returnable) ⁽¹⁾ | According to packaging instruction |
| Quality Control | |
| Traceability ⁽¹⁾ | Lot no. marked on the back side of the roll and on the small sticker on the roll |
| Defects marked by label ⁽¹⁾ | Maximum 3 point defects / 50m roll ⁽²⁾ |
| Each defect is balanced by | Adding 50 cm / defect ⁽²⁾ |
| Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect. | |

Properties

- Tear resistant
- High tensile strength
- Fire resistant
- Easily re-paintable
- Permeable
- Environmentally friendly



Edited by:

ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovska 106

CZ – 570 01 Litomyšl

Tel: +420 461 651 111

Fax: +420 461 612 769

www.adfors.com

ADFORS reserves the right to change the information given herein without prior notice

Last update: 19/12/2017

⁽¹⁾ Other dimensions or features on request

⁽²⁾ Details are described in CAS 0337