

### Technical Data Sheet

#### General Description

Glass fiber wall covering is used to cover walls and other interior surfaces. Product is perfect for new spaces: thanks to its high mechanical properties it prevents cracks from appearing, consequently prolonging the surface lifetime. It is also a performing solution for light renovation: it covers crack and wall irregularities.

Products with sand-coating are perfect solution for high decorative purpose thanks to their two-tone surface finish aspect after painting.

The patented technology CleanAir helps to maintain a healthy indoor environment by capturing formaldehyde.

#### Technical characteristics

Technical Characteristics	
Composition	100 % coated glass fiber
Treated fabric weight (average value)	390 g / m <sup>2</sup> (± 8 %)
Oekotex certificate Standard 100	Product Class I
Emission in indoor air	A+ (very low)
Fire resistance (EN 13501-1)	Euroclass B-s 1,d 0
Recommendation for application	
Quantity of glue	250 g / m <sup>2</sup> (approximate)
Quantity of acrylic paint	200 - 300 g / m <sup>2</sup> (approximate)
Dimensions & Packaging	
Width (individual value)	100 cm (± 1 % or closed pattern repeat)
Roll length (individual value) <sup>(1)</sup>	10.5 m (± 1 %)
Paintable surface <sup>(2)</sup>	Inside
Roll packaging <sup>(2)</sup>	Plastic foil
Label on roll <sup>(2)</sup>	With installation instructions
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll.
Quality Control	
Traceability <sup>(2)</sup>	Lot no. marked on the back side of the roll and on the small sticker on the roll
Defects marked by label <sup>(2)</sup>	Maximum 3 point defects / 50m roll
Each defect is balanced by <sup>(2)</sup>	Adding 50 cm / defect
Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect.	

#### Properties

- Tear resistant
- High tensile strength
- Fire resistant
- Easily re-paintable
- Breathable
- Flat finish
- Two-tone finish
- Absorbs formaldehyde



Edited by:

**ADFORS Construction Products Europe**

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovska 106

CZ – 570 01 Litomyšl

Tel: +420 461 651 111

Fax: +420 461 612 769

www.adfors.com

**ADFORS** reserves the right to change the information given herein without prior notice

Last update: 19/12/2017

<sup>(1)</sup> Other dimensions or features on request

<sup>(2)</sup> Details are described in CAS 0337