

# Declaration of Performance

No. 1 DOP – R 585 A101 – 01

Unique identification code of the product-type:	P-R 585 A101 : 2024
Intended use of the product:	For reinforcement of cement based renderings
Producer:	SAINT-GOBAIN ADFORS CZ, s.r.o. Sokolovská 106 570 01 Litomyšl Czech Republic
System of assessment and verification of constancy of performance of the construction product:	System 2+
Technical assessment body:	TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p., notified body 1020, issued ETA 13/0392

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	NPD	EAD 040016-01-0404: 2021
Organic content, %:	19 ± 3	
Heat combustion $Q_{PCS}$ , MJ/kg:	4,88	
Mesh opening, mm:	(5,5 / 4,5) ± 0,5	
Roll width, cm:	NPD	
Weaving accuracy	NPD	
Tensile strength in the as-delivered state (warp/weft), N/50 mm	min. 8000 / min. 8000	
Elongation in the as-delivered state (warp/weft), %	max. 5,5 / max. 5,0	
Tensile strength after alkalis conditioning (warp/weft), N/50 mm	min. 4000 / min. 4000 min. 50 % / min. 50 %	
Elongation after alkalis conditioning (warp/weft), %	max. 4 / max. 4	
Mass per unit area, g/m <sup>2</sup> :	670 ± 3%	
Thickness, mm:	1,3 ± 0,2	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Litomyšl 29.3.2024

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovská 106, 570 01 LITOMYŠL

IČ: 000 12 661 ... DIČ: CZ00012661

Lucie Waniáusová  
Business Development Manager