

Declaration of Performance

No. 1 DOP – G120– 02

Unique identification code of the product-type:	P- G120 : 2024
Intended use of the product:	For reinforcement of cement-,anhydrite or resin-based screed
Producer:	SAINT-GOBAIN ADFORS CZ, s.r.o. Sokolovská 106 570 01 Litomyšl Czech Republic
System of assessment and verification of constancy of performance of the construction product:	System 2+
Technical assessment body:	TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p., notified body 1020, issued ETA 22/0243

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	NPD	EAD 260057-00-0303
Organic content, %:	19 ± 4	
Heat combustion Q _{PCS} , MJ/kg:	5,86	
Mesh opening, mm:	(40,0 / 40,0) ± 1,0	
Roll width, cm:	NPD	
Weaving accuracy	NPD	
Tensile strenght in the as-delivered state (warp/weft), kN/m	min. 30 / min. 30	
Elongation in the as-delivered state (warp/weft), %	max. 6,0 / max. 6,5	
Tensile strenght after alkalis conditioning (warp/weft), kN/m	min. 20 / min. 20 min. 50 % / min. 50 %	
Elongation after alkalis conditioning (warp/weft), %	max. 4 / max. 4,5	
Tensile strenght after acid conditioning (warp/weft), kN/m	min. 20 / min. 20	
Elongation after acid conditioning (warp/weft), %	max. 3,5 / max. 3,8	
Mass per unit area, g/m ² :	153 ± 5%	
Thickness, mm:	1,8 ± 0,3	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Litomyšl 20.11.2024

SAINT-GOBAIN ADFORS CZ s.r.o.
Sokolovská 106, 570 01 LITOMYŠL
IČ: 000 12 661 • DIČ: CZ00012661
...../104/...

Lucie Waniausová
Business Development Manager